

Nu-Metrics Traffic Analyzer Study

Computer Generated Summary Report

City: City of Fairfax

Street: Dwight Ave. #6 Red

A study of vehicle traffic was conducted with HI-STAR unit number 1042. The study was done in the West Bound lane on Dwight Ave. using counter #6 Red as shown on attached drawing. The counter was placed 260 Ft. from Roberts Rd. The study began on 12/02/2003 at 12:00 PM and concluded on 12/05/2003 at 09:00 AM, lasting a total of 69 hours. Data was recorded in 60 minute time periods. The total recorded volume of traffic showed 2,224 vehicles passed through the location with a peak volume of 83 on 12/03/2003 at 04:00 PM and a minimum volume of 1 on 12/04/2003 at 01:00 AM. The AADT Count for this study was 945.

SPEED

Chart 1 lists the values of the speed bins and the total traffic volume for each bin.

Chart 1								
0 to 9	10 to 14	15 to 19	20 to 24	25 to 29	30 to 34	35 to 39	40 to 44	45 to 49
0	24	124	504	773	476	115	31	7

At least half of the vehicles were traveling in the 25 - 29 mph range or a lower speed. The average speed for all classified vehicles was 27 mph with 68.8 percent exceeding the posted speed of 25 mph. The HI-STAR found 9.17 percent of the total vehicles were traveling in excess of 35mph. The mode speed for this traffic study was 25 mph and the 85th percentile was 33.72 mph.

CLASSIFICATION

Chart 2 lists the values of the eight classification bins and the total traffic volume accumulated for each bin.

Chart 2							
0 to 20	21 to 27	28 to 39	40 to 49	50 to 59	60 to 69	70 to 79	80 >
1970	87	18	5	4	1	1	7

Most of the vehicles classified during the study were Passenger Cars. The number of Passenger Cars in the study was 2,057 which represents 98.30 percent of the total classified vehicles. The number of Small Trucks in the study was 18 which represents 0.90 percent of the total classified vehicles. The number of Trucks/Buses in the study was 5 which represents 0.20 percent of the total classified vehicles. The number of Tractor Trailers in the study was 13 which represents 0.60 percent of the total classified vehicles.

HEADWAY

During the peak time period, on 12/05/2003 at 09:00 AM the average headway between the vehicles

was 6.99 seconds. The slowest traffic period was on 12/05/2003 at 11:00 AM. During this slowest period, the average headway was 3600.0 seconds.

WEATHER

The roadway surface temperature over the period of the study varied between 31 and 70 degrees Fahrenheit. The HI-STAR determined that the roadway surface was Dry 100.00 percent of the time.